

1.67 非球面レンズ

■ ニューオーブル167AS エコ <CSコート> 

 在庫範囲

C(-)	球面	T C (-)											
		0			1			2			3		
S(-)	(-)	0	5	0	2	5	7	0	2	5	7	0	3
		5	0	5	0	5	0	5	0	5	0	5	0
0.00													
.25													
.50													
.75													
1.00													
.25													
.50													
.75													
2.00													
.25													
.50													
.75													
3.00													
.25													
.50													
.75													
4.00													
.25													
.50													
.75													
5.00													
.25													
.50													
.75													
6.00													
.25													
.50													
.75													
7.00													
.25													
.50													
.75													
8.00													
.25													
.50													
.75													
9.00													
.25													
.50													
.75													
10.00													

C(+)	球面	T C (+)											
		0			1			2					
S(+)	(+))	0	5	0	2	5	7	0	2	5	7	0	
		5	0	5	0	5	0	5	0	5	0	5	0
0.00													
.25													
.50													
.75													
1.00													
.25													
.50													
.75													
2.00													
.25													
.50													
.75													
3.00													
.25													
.50													
.75													
4.00													
.25													
.50													
.75													
5.00													
.25													
.50													
.75													
6.00													

混 合 乱 視													
C(-)	球面	T C (-)											
		0			1			2					
S(+)	(+)	0	5	0	2	5	7	0	2	5	7	0	
		5	0	5	0	5	0	5	0	5	0	5	0
0.25													
.50													
.75													
1.00													
.25													
.50													
.75													

注 特注及び在庫範囲以外はお受け出来ません。

● カラーはお受けできません。

仕 様	屈 折 率	1.67
	ア ッ ペ 数	32.0
	比 重	1.35

特殊加工	プ リ ズ ム	—	
	偏 心	—	
	外 径 指 定	—	
	コバ厚・中心厚	—	
	U V 加 工	●	UV練り込み
	プライマー加工	—	
	C S コ ー ト	●	標準
	C Z コ ー ト	—	
	Z Z コ ー ト	—	
	シェイプ加工	—	
	静電防止コート	●	 標準