

1.60 非球面レンズ

■ コンフル 160AS トランジェ <CZコート> 電

在庫範囲

C(-)	球面	T C (-)											
		0			1			2			3		
S(-)	(-)	2	5	7	0	2	5	7	0	2	5	7	0
0.00		5	0	5	0	5	0	5	0	5	0	5	0
.25													
.50													
.75													
1.00													
.25													
.50													
.75													
2.00													
.25													
.50													
.75													
3.00													
.25													
.50													
.75													
4.00													
.25													
.50													
.75													
5.00													
.25													
.50													
.75													
6.00													
.25													
.50													
.75													
7.00													
.25													
.50													
.75													
8.00													
.25													
.50													
.75													
9.00													
.25													
.50													
.75													
10.00													

C(+)	球面	T C (+)											
		0			1			2					
S(+)	(+)	2	5	7	0	2	5	7	0	2	5	7	0
0.00		5	0	5	0	5	0	5	0	5	0	5	0
.25													
.50													
.75													
1.00													
.25													
.50													
.75													
2.00													
.25													
.50													
.75													
3.00													
.25													
.50													
.75													
4.00													
.25													
.50													
.75													
5.00													
.25													
.50													
.75													
6.00													

混 合 乱 視													
C(-)	球面	T C (-)											
		0			1			2					
S(+)	(+)	2	5	7	0	2	5	7	0	2	5	7	0
0.25		5	0	5	0	5	0	5	0	5	0	5	0
.50													
.75													
1.00													
.25													
.50													
.75													

注 カラーおよび特注範囲にも対応しております。

カラーや特注をご注文の場合は、「コンフル 160AS」の範囲表をご参照ください。
「コンフル 160AS」の範囲で製作いたします（外径や範囲、特殊加工も同じです）。

仕 様	屈 折 率	1.60
	ア ッ ペ 数	42.0
	比 重	1.30

特殊加工	プ リ ズ ム	—	
	偏 心	—	
	外 径 指 定	—	
	コ バ 厚・中 心 厚	—	
	U V 加 工	●	UV練り込み
	プライマー加工	—	
	C S コ ー ト	—	
	C Z コ ー ト	●	標準
	Z Z コ ー ト	—	
	シェイプ加工	—	
	静電防止コート	●	電 標準