

1.56 球面レンズ

■ アルファワン **LCD** **zero** ※ ZERO はダブルハーフのみ可 在庫のみ **電**

内面マルチ可

在庫範囲

C(-)	球面	T C (-)											
		0			1			2			3		
S(-)	(-)	2	5	7	0	2	5	7	0	2	5	7	0
		5	0	5	0	5	0	5	0	5	0	5	0
0.00													
.25													
.50													
.75													
1.00													
.25													
.50													
.75													
2.00													
.25													
.50													
.75													
3.00													
.25													
.50													
.75													
4.00													
.25													
.50													
.75													
5.00													
.25													
.50													
.75													
6.00													
.25													
.50													
.75													
7.00													
.25													
.50													
.75													
8.00													

C(+)	球面	T C (+)											
		0			1			2					
S(+)	(+))	2	5	7	0	2	5	7	0	2	5	7	0
		5	0	5	0	5	0	5	0	5	0	5	0
0.00													
.25													
.50													
.75													
1.00													
.25													
.50													
.75													
2.00													
.25													
.50													
.75													
3.00													
.25													
.50													
.75													
4.00													

混 合 乱 視													
C(-)	球面	T C (-)											
		0			1			2					
S(+)	(+))	2	5	7	0	2	5	7	0	2	5	7	0
		5	0	5	0	5	0	5	0	5	0	5	0
0.25													
.50													
.75													
1.00													
.25													
.50													
.75													

- 注 1** 在庫範囲以外はお受け出来ません。
- 注 2** C-2.25 以上の在庫価格のカラーは特注範囲価格になります。
- 注 3** 染色品は全て<CS コート>になっています。
- 注 4** 染色品は全て UV 練り込み になっています。

他品種との染色組み合わせはお受けできません。

仕 様	屈 折 率	1.56
	ア ッ ペ 数	35.0
	比 重	1.27

LCD LCD カラー可
zero ゼロセレクト可 (※ダブルハーフのみ)

※ 特殊カラーの片眼染色はお受けできません。

特殊加工	プ リ ズ ム	—	
	偏 心	—	
	外 径 指 定	—	
	コ バ 厚・中 心 厚	—	
	U V 加 工	●	染色品はUV練り込み
	プライマー加工	—	
	C S コ ー ト	●	染色品は 標準
	C Z コ ー ト	—	
	Z Z コ ー ト	—	
	シェイプ加工	—	
	静電防止コート	●	電 在庫のみ 標準